



New and Powerful!

Distributed By:

ABOMAR
EQUIPMENT SALES
CORPORATION
Dealer in the Philippines since 1974

CAGAYAN DE ORO BRANCH

#6 A&G Arcade, National Highway,
Lapasan, Cagayan de Oro City
Phone/Fax: +63 (8822) 732365;
Tel: +63 (88) 8524835

BACOLOD BRANCH

Lacson Ext. cor Goldenfield St. Liroville
Subd., Singang, Bacolod City
Philippines 6100
Telephone: +63 (34) 4331687
Fax: +63 (34) 4323673

CEBU BRANCH

111 Krizia Bldg., Gorordo Ave.
Lahug, Cebu City 6000
Phone: +63(32)2338461 or 4171006
Fax: +63 (32) 2338461

PASIG BRANCH

MIC-1 Manjos Industrial Compound
A. Sandoval Ave., Pinagbuhatan
Pasig City 1602 Philippines
Telephone/Fax: +63 (2) 6409638
Phone: +63 (2) 6422008

DAVAO BRANCH

#10 E.C.Business Center C.M. Recto Ave.,
Davao City 8000 Philippines
Telephone: +63 (82) 2263791
Fax: +63 (82) 2210446

** This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification and design of all products described in this literature without notice. *John Deere's green and yellow colour scheme, the leaping deer symbol and JOHN DEERE are trademarks of Deere & Company."

Specifications



	5055E	5065E	5075E
Engine			
Power(HP)/rpm	55 HP/ 2400 RPM	65 HP/ 2400 RPM	75 HP/ 2400 RPM
Engine Model	JD3029D	JD3029T	
Fuel tank capacity	68L		
Air Filter	Dry type, dual element		
Aspiration	Natural	Turbo Charged	
Battery	12V, 88Ah	V12V, 100Ah	
Transmission			
Clutch	Dual		
Gear Box	9 Forward + 3 Reverse, Collar shift		9 Forward + 3 Reverse, TSS
	(Optional : TSS, Creeper)		
Speeds	Forward 2.05 to 31.52 kmph	Forward 2.21 to 31.17 kmph	Forward 2.13 to 29.97 kmph
	Reverse 3.45 to 24.39 kmph	Reverse 3.58 to 24.12 kmph	Reverse 3.58 to 24.12 kmph
Hydraulics			
Lifting Capacity			
(at lower link ends)	1800 kg		
3 Point linkage	Cat II		
Steering			
Steering Type	Power		



Specifications



	5055E	5065E	5075E
Brakes			
Type	Self-Adjusting, Self-equalizing Hydraulically Actuated. Oil immersed disk brakes		
Power Take Off			
PTO type for 2WD	Single PTO, 540 AT 2376 ERPM		N/A
4WD	Dual PTO, 540 at 2376 ERPM & 540E at 1705 ERPM		
Wheels and Tyres			
Front 2WD model	6.5 x 20	6.5 x 20	11.2 x 24 and 16.9 x 30
Front 4WD model	9.5 x 24	11.2 x 24	(4WD)
Rear 2WD model	16.9 x 28	18.4 x 30	12.4 x 24 and 18.4 x 30
Rear 4WD model	16.9 x 28	16.9 x 30	(4WD)
Dimensions and Weights			
Wheel base		2050 mm	N/A
Overall Length (mm)	4026 mm front weight to TPL (with ballast)		
Overall Width (mm)	1901 mm from rear RH tyre to LH tyre (with ballast)(2+2 rear weights)		
Shipping Weight (2WD)	2110	2290	
Shipping Weight (4WD)	2335	2425	
Ground clearance 2WD		487	512
Ground clearance 4WD	348	378	403

